



HIGH-EFFICIENCY SOLDERING IRONS

High-powered quick thermal recovery HIGH-POWER SOLDERING IRONS CXR-80/100



- HIGH THERMAL-STORAGE EFFECT**
Good for terminals, connectors
- THICK-PLATED LONG-LIFE TIP**
Hard chrome coated
- EASY HEATER REPLACEMENT**
Connector-type heater



CXR-100

Note: Supplied with Chisel Tip not as shown

SPECIFICATIONS

Model	CXR-80	CXR-100
Voltage	220-240V AC 50/60Hz	
Power Consumption	32W	38W
Insulation Resistance	Over 100M Ω (500V DC)	
Heater	Ceramic Heater	
Power Cord Length	1.5m	
Length	268mm	
Weight	80g	88g
Accessories	Soldering Iron Tip	
	CXR-80RT-5D	CXR-100RT-7D

*The length does not include the cord bushing. The weight does not include the cord.

REPLACEMENT TIPS

CXR-80RT-5D	CXR-80RT-7D	CXR-100RT-7D

REPLACEMENT PARTS / OPTIONS

CXR-80 Heater CXR-80H	CXR-100 Heater CXR-100H
Recommended Stand RD-7303N	

Slim grip for easy handling. STAINED-GLASS SOLDERING IRONS HRC-80/HRC-100



- Special soldering iron for stained-glass work.
- Good for Tiffany-style to lead-came style.
- Equipped with slim grip for easy handling with small hands.



HRC-80

HRC-100

HRC-80

HRC-100

SPECIFICATIONS

Model	HRC-80	HRC-100
Voltage	220-240V AC 50/60Hz	
Power Consumption	32W	38W
Insulation Resistance	Over 100M Ω (500V DC)	
Heater	Ceramic Heater	
Power Cord Length	1.5m	
Length	273mm	273mm
Weight	80g	88g
Accessories	Soldering Iron Tip	
	CXR-80RT-5CJ	CXR-100RT-7CJ

*The length does not include the cord bushing. The weight does not include the cord.

REPLACEMENT TIPS

	HRC-80 CXR-80RT-5CJ	HRC-100 CXR-100RT-7CJ

REPLACEMENT PARTS / OPTIONS

HRC-80 Heater CXR-80H	HRC-100 Heater CXR-100H
---------------------------------	-----------------------------------