

HAKKO FR-300

DESOLDERING TOOL

NEW

Handy Desoldering Tool

Four new features that increase workability and efficiency


1

Quick Change Nozzle System provides speed and safety.



Nozzle changing tool

The new Quick Change Nozzle System allows for a safer and simpler method to quickly remove nozzles for cleaning or replacement, even when the unit is hot.



Filter pipe




Dispose of solder dross with a simple operation without being affected by heat.

3

Calculated weight balance

Motor, pump, and temperature control circuit are optimally positioned within the body to ensure good balance when holding the gun.

Well-balanced
Ergonomic design for operators' comfort



2

Dial control for easy temperature selection

The dial integrated into the handle makes it easy to adjust the temperature setting without the use of additional tools.

Setting 1	350°C	Setting 2	400°C
Setting 3	450°C	Setting 4	500°C

LED indicators let you easily see when the heater is active and idling at your temperature setting.



Features LED lamp that indicates heater's activity


Dial for temperature control

4

Integrated power switch

Locating the power switch on the handle makes it possible to turn the tool on and off with ease and

does away with the hassle of having to remove the plug when you want to turn off the tool.



FR-300

Simple iron holder included

Includes simple iron holder that prevents burns and accidents from hot parts.



Packing List



HAKKO FR-300 Handy Desoldering Tool

CONTENTS: Cleaning pin for $\phi 1.0$ mm nozzles, Cleaning pin for heating core, Ceramic paper filter (large x2), Simple iron holder, Aluminum pre-filter, Nozzle wrench, Instruction manual

Option



Part No.	Part name
C1100	Iron holder



Part No.	Part name	Nozzle dimensions
B1302	Cleaning drill	For $\phi 0.8$ mm
B1303		For $\phi 1.0$ mm
B1304		For $\phi 1.3$ mm
B1305		For $\phi 1.6$ mm
B1085	Cleaning pin	For heating element
B1086		For $\phi 0.8$ mm nozzle
B1087		For $\phi 1.0$ mm nozzle
B1088		For $\phi 1.3$ mm nozzle
B1089		For $\phi 1.6$ mm nozzle

* B1087 is included in FR-300.

Replacement Parts

Part No.	Part name
A5000	Heating element 100-120 V
A5001	Heating element 220-240 V
A1217	Front holder
B5014	Element cover
B5016	Pre-filter (ALUM) set of 5
B5017	Filter pipe
A1033	Ceramic paper filter (L) set of 10

Replacement Nozzles (Unit: mm)

Part No.	Shape	ϕA (mm)	ϕB (mm)
N50-01		0.8	2.0
N50-02		1.0	2.0
N50-03		0.8	2.5
N50-04		1.0	2.5
N50-05		1.3	3.0
N50-06		1.6	3.0

*Included nozzle is N50-04.

Specifications

Model No.	FR-300
Power consumption	100 V 98 W (50/60 Hz), 110 V 122 W (50/60 Hz), 120 V 140 W (50/60 Hz), 220 V 105 W (50/60 Hz), 230 V 118 W (50/60 Hz), 240 V 130 W (50/60 Hz)
Temperature range	350–500°C (660–930°F)
Nozzle to ground resistance	<2 Ω
Nozzle to ground potential	<2 mV
Vacuum generator	Diaphragm pump
Vacuum pressure	81 kPa (610 mmHg)
Suction flow	11 L/min.
Standard nozzle	$\phi 1.0$ mm (Part No. N50-04)
Dimensions	210(W)×226(H)mm / 8.9 x 8.3 in.
Weight (w/o cord)	0.52 kg (1.1 lb.)

CA00442LbYa001 2014.9

HAKKO
HAKKO CORPORATION
OVERSEAS AFFILIATES

U.S.A.
 AMERICAN HAKKO PRODUCTS, INC.
 28920 AVE. WILLIAMS VALENCIA, CA 91355, U.S.A.
 TEL: (661) 294-0090 FAX: (661) 294-0096
 Toll Free (800) 88-HAKKO
 4 2 5 5 6
<http://www.HakkoUSA.com>

HEAD OFFICE

4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN
 TEL:+81-6-6561-3225 FAX:+81-6-6561-8466
<http://www.hakko.com> E-mail:sales@hakko.com

HONG KONG
 HAKKO DEVELOPMENT CO., LTD.
 ROOM 1504, EASTERN HARBOUR CENTRE,
 28 HOI CHAK STREET, QUARRY BAY, HONG KONG.
 TEL: 2811-5588 FAX: 2590-0217
<http://www.hakko.com.hk>
 E-mail:info@hakko.com.hk

SYNERGY
ELECTRONICS LTD
sales@synergielectronics.co.nz
www.synergielectronics.co.nz
 Ph 0800 347 045

Please access to the following for the other Sales affiliates.
<http://www.hakko.com>

Specifications and design are subject to change without notice. Copyright Hakko Corporation. All right reserved.