


■ Replacement nozzles

(Unit: mm)



FR-410

■ Packing list



Station, Desoldering tool (FR-410), Iron holder (with cleaning wire), Power cord, Tool box (Cleaning pin for ø1.0mm, Cleaning pin for heater, Cleaning drill for ø1.0mm, Nozzle wrench, Filter [qty 2], Ceramic paper filter [qty 4], Instruction manual

■ Specifications

Power consumption	190 W
Temperature range	330 to 450°C
Temperature stability	±5°C at idle temperature
■ Station	
Output voltage	AC 24 V
Vacuum generator	Double cylinder type
Vacuum pressure	80 kPa ( 600 mmHg )
Suction flow	15 L /min.
Dimensions	165 ( W ) × 137 ( H ) × 244 ( D ) mm
Weight	4.8 Kg
■ Desoldering tool	
Power consumption	140 W ( 24V )
Nozzle to ground resistance	< 2 Ω
Nozzle to ground potential	< 2 mV
Heating element	Composite heater
Standard nozzle	ø 1.0 mm S type ( Part No.N61-05 )
Cord length	1.2 m
Total length (without cord)	168 mm ( with ø 1.0 mm S type nozzle )
Weight (without cord)	170 g ( with ø 1.0 mm S type nozzle )

CA00478QbYa001 2016.1

**HAKKO**  
HAKKO CORPORATION  
OVERSEAS AFFILIATES

**HEAD OFFICE**  
4-5, SHIOKUSA 2-CHOME, NANIWA-KU, OSAKA, 556-0024 JAPAN  
TEL:+81-6-6561-3225 FAX:+81-6-6561-8466  
<http://www.hakko.com> E-mail:sales@hakko.com

**U.S.A.**  
AMERICAN HAKKO PRODUCTS, INC.  
28920 AVENUE WILLIAMS VALENCIA, CA 91355, U.S.A.  
TEL: (661) 294-0090 FAX: (661) 294-0096  
Toll Free (800)88-HAKKO  
<http://www.hakkousa.com>

**HONG KONG**  
HAKKO DEVELOPMENT CO., LTD.  
ROOM 1504, EASTERN HARBOUR CENTRE,  
28 HOI CHAK STREET, QUARRY BAY, HONG KONG.  
TEL: 2811-5588 FAX: 2590-0217  
<http://www.hakko.com.hk>  
E-mail:info@hakko.com.hk

**SINGAPORE**  
HAKKO PRODUCTS PTE LTD  
1, GENTING LINK #02-04  
PERFECT ONE, SINGAPORE 349518  
TEL: 6748-2277 FAX: 6744-0033  
<http://www.hakko.com.sg>  
E-mail:sales@hakko.com.sg

Please access to the following for the other sales affiliates and distributors.  
<http://www.hakko.com>

Specifications and design are subject to change without notice. Copyright HAKKO Corporation. All right reserved.  
HAKKO is registered in countries and regions including the following, Japan, USA, South Korea, Singapore, China, the member of CTM.

**HAKKO**®

Desoldering • Rework

Station Type  
Desoldering Tool

**HAKKO FR-410** ESD SAFE  
DESOLDERING TOOL

High Power of 140 Watts !  
Ideal for Micro Land Pattern  
and Narrow Space

NEW




# 140 W high powers enable perfect desoldering for the components on multi-layer PWB

3 times more powerful than the previous models!  
The high power makes it easy to desolder on multi-layer PWB.

\*HAKKO 474 · 475

## Heating power

almost **3 times** increased  
comparison with our previous models



## Unique functions increase desoldering work efficiency

### Secure desoldering - High suction pressure with valve function


Suction starts 0.2 seconds after pulling the trigger for immediate and high pressure suction to achieve complete desoldering.




### Reduction of solder clogging

#### 1. Improvement in heating core

Heating ability for backside of heating core is increased to ensure suctioned solder be carried to filter pipe.



**HAKKO FR-410**  
No solder clogging due to higher temperature at the back side of heating core



**previous model**  
Solder clogs at the backside of heating core


Image

#### 2. Featuring ACF (Anti Clogging Function)

ACF ensures suctioned solder be carried to filter pipe by keeping pump running for a certain period of time (1 to 5 seconds) automatically after releasing trigger.

# A wide selection of nozzle is available for a variety of desoldering works


New added nozzles make it possible to desolder even on micro lands, components in narrow space and flat type terminals



**SS type nozzles for micro land-patterns**  
Close-fitting nozzles on micro land pattern secure desoldering.



**Long type nozzles for narrow space**  
Slim and long nozzles reach to target easily in a narrow space.



**Oval shape nozzles for flat type terminals**  
No solder left-over because of the nozzles that match square shape terminals.



### Improvement in maintainability

#### 1. Easy nozzle replacement

The dedicated wrench allows safe, easy and smooth nozzle replacement.



#### 2. Easy heater replacement

Easy heater replacement by removing 3 screws on the part of heating core.



#### 3. Lager filter and more transparency

Filter size has been increased to protect the pump from contaminants, and transparent filter cover allows quick visual check of the filter condition.



#### 4. Tool box

FR-410 comes with a tool box that contains of maintenance tools to keep nozzle and heater in a good condition.



### Easy-to-read large LCD

The large LCD display clearly shows set temperature and indicates a level of solder clogging.



Suction with no clogging



Suction with clogging